



Product Specification Data



Description

Briteline® application tape is standard weight saturated paper coated with a high tack rubber adhesive designed specifically as a premasking of small and mid-sized die cut or prespaced vinyl and printed graphics.

Applications

Premask for small and medium size vinyl graphics. All-purpose application tape for wet and dry applications. Excellent for transferring graphics to banners.

Thickness

Facestock	100-113 microns (4.0-4.5mm)
Facestock + Adhesive	125-138 microns (5.0-5.5 mils)

Dimensional Stability

n/a

Storage Stability

1-year

Tear Resistance

50

Recommendations

Removes easily following graphics application. If adhesive touches adhesive, Briteline® application tape pulls apart easily with no adhesive delamination. Works well in either wet or dry applications with no adhesive transfer.

Adhesion

To stainless steel: 18-20 N/100mm (16-18 oz).

Temperature Ranges

Minimum application temperature is 40°F.
Service temperature range is -40°F to 180°F.

Expected Exterior Exposure

Under normal conditions, up to 5 years resistance can be expected. Removable up to 1 year.

Surface Gloss

n/a

Tensile

297 n/100mm (171lb.in)

Product Series

RGT

Statement of Practical Use

We believe the information on this product to be accurate. However, since we cannot anticipate or control the conditions under which this information or our products may be used, we cannot guarantee results obtained through their use. Tests of our products should be made by users to determine the suitability of these products for a specific purpose. The products are sold without warranty, either express or implied. The purchaser should refer to Grimco, Inc's price list for terms and conditions of sale, including disclaimer of warranties and limitation of liability.